| | | | | | | | | 3 | 352 | 2A- | -01 |
|---|---|---|---|---|---|---|--|---|-----|-----|-----|
| S | Ε | R | V | 1 | С | Ε | | Ν | 0 | Т | Ε |

Supersedes: None

33522A – 30 MHz Function/Arbitrary Waveform Generator

Serial Numbers: ALL

External clock reference indicator may be incorrect when exceeding the published specifications.

Parts Required:

P/N Description Qty.

None

ADMINISTRATIVE INFORMATION

| SERVICE NOTE CLASSIFICATION: | | | | | | | | |
|------------------------------|------------------|--|--|--|--|--|--|--|
| INFORMATION ONLY | | | | | | | | |
| AUTHOR: LH | PRODUCT LINE: SP | | | | | | | |
| ADDITIONAL INFORMATION: | | | | | | | | |
| | | | | | | | | |

© AGILENT TECHNOLOGIES, INC. 2010 PRINTED IN U.S.A.



September 16, 2010

Rev. 17

Page 2 of 2 33522A-01

Situation:

The 33522A has a frequency reference input with the ability to synchronize to a 10 MHz signal. The standard TCXO frequency reference will synchronize to 10 MHz \pm 20 Hz. The optional ultra-high stability OCXO frequency reference will synchronize to 10 MHz \pm 1 Hz.

If the external frequency reference is far beyond this range and exceeds 10 MHz \pm 300 Hz (typical), the instrument may incorrectly indicate a "Locked" state.

Solution/Action:

Using an external 10 MHz signal within the range of the published specifications will reliably indicate "Locked", "Unlocked" and "Detected" states.